



T150	BUSE ARCHE SECTION PASSAGE	TR
COMPOSITION DE L'ANNEAU		
	VOÛTE	COINS
	RADIER	

Code	Portée	Flèche	Section	Périmètre	Troncature	Plaques	Rt	α_t	Rc	α_c	Rb	α_b
	m	m	m ²	m	m	u	mm	°	mm	°	mm	°
TR/ 1	2,98	2,64	6,37	9,00	0,87	6	1491	201,71	1023	70,00	3916	18,29
TR/ 2	3,45	2,85	7,80	10,00	1,21	6	1724	174,49	1023	70,00	2833	45,51
TR/ 3	3,53	2,91	8,18	11,00	1,17	6	1763	178,71	1023	70,00	3122	41,29
TR/ 4	3,88	3,14	9,79	12,00	1,13	6	1941	184,45	1023	70,00	4029	35,55
TR/ 5	3,96	3,20	10,21	11,50	1,08	6	1979	188,18	1023	70,00	4501	31,82
TR/ 6	4,18	3,39	11,54	12,25	0,96	6	2091	198,68	1023	70,00	6718	21,32
TR/ 7	4,26	3,45	12,00	12,50	0,91	7	2128	201,96	1023	70,00	7939	18,04
TR/ 8	4,71	3,66	13,90	13,50	1,13	8	2355	188,59	1023	70,00	5927	31,42
TR/ 9	4,79	3,79	14,93	14,50	0,92	8	2397	203,22	1023	70,00	10241	16,78
TR/10	4,99	3,91	15,97	14,50	0,96	8	2495	200,91	1023	70,00	9753	19,09
TR/11	5,26	4,08	17,60	15,25	0,96	8	2630	201,54	1023	70,00	10861	18,46
TR/12	5,73	4,29	19,85	16,25	1,18	8	2866	189,95	1023	70,00	8103	30,05
TR/13	5,94	4,40	21,04	17,25	1,22	8	2969	188,17	1023	70,00	8101	31,83
TR/14	6,06	4,60	22,94	18,25	0,96	9	3032	203,17	1023	70,00	14466	16,83
TR/15	6,28	5,30	26,68	18,50	1,72	9	3138	196,30	1671	60,00	5572	43,70
TR/16	6,51	5,49	28,83	19,25	1,60	9	3253	202,56	1671	60,00	6505	37,44
TR/17	6,77	5,67	31,06	20,00	1,61	9	3387	203,02	1671	60,00	6971	36,99
TR/18	6,92	5,80	32,59	21,00	1,54	10	3462	206,86	1671	60,00	7780	33,14
TR/19	7,23	6,06	35,78	22,00	1,39	10	3613	214,10	1671	60,00	9954	25,90
TR/20	7,38	6,11	36,57	21,75	1,60	11	3691	205,67	1671	60,00	8345	34,33
TR/21	7,53	6,24	38,23	22,25	1,52	11	3765	209,22	1671	60,00	9308	30,78
TR/22	7,80	6,42	40,78	23,00	1,54	11	3898	209,45	1671	60,00	9847	30,55
TR/23	7,99	6,54	42,52	24,00	1,58	11	3994	208,01	1671	60,00	9850	31,99
TR/24	8,23	6,65	44,27	25,00	1,76	11	4115	201,89	1671	60,00	9021	38,11
TR/25	8,43	6,77	46,07	24,50	1,81	11	4213	200,61	1671	60,00	9091	39,39